

# BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
<b>3B12-328</b>  Flexmember 578-93-3-100		<b>ASA-92-8-017</b> 	<b>ASA-92-6-111</b> 	Firestone 7994 Triangle 4546 Watson & Chalin AS-0019-1F
<b>3B12-329</b>  Flexmember 578-93-3-100		<b>ASA-92-8-159</b> 	<b>ASA-92-6-111</b> 	Firestone 7995 Triangle 4547 Watson & Chalin AS-0048-1F
<b>3B12-335</b>  Flexmember 578-93-3-100		<b>ASA-92-8-005</b> 	<b>ASA-92-6-111</b> 	Firestone 7996 Granning 8221 Triangle 4520
<b>3B14-351</b>  Flexmember 578-93-3-350		<b>ASA-92-8-028</b> 	<b>ASA-92-6-013</b> 	
<b>3B14-352</b>  Flexmember 578-93-3-350  Replaced by 3B14-361		<b>ASA-92-8-030</b> 	<b>ASA-92-6-013</b> 	<b>OBSOLETE</b>  Replaced by 3B14-361

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/4 NPTF
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- - Stud - 3/4-10
- ⊗ - Stud - 3/4-16; Air Fitting - 1/4 NPTF
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF